



## IMPROVED SUBMERSIBLE FARM

5

### FIELD OF INVENTION

This invention relates to an improved submersible shellfish farm including ~~consisting of~~ at least one line of cables bearing ropes to which the shellfish are attached for their rearing. ~~said~~ The line being is suspended horizontally from two end floats which support ~~it~~ the line in association with intermediate support buoys and is anchored by dead weights positioned at each end of the line.

### BACKGROUND OF INVENTION

15 In the traditional shellfish breeding methods requiring shallow seabeds in quiet waters, matter is produced, which, in high concentrations, perturbs and offsets the balance of the surrounding ecosystem. This environmental pollution has a negative effect on the  
20 ecological balance by causing a decrease in the plankton flow and a drop of the feeding rate of the shellfish, with a consequent reduction of the desired production of cultures.

Other self-supported installations are also constructed for breeding shellfish, such as that disclosed in the document ES 1043285U by Carceller, which describes a

live well improved for growing mussels in open sea,  
comprising a rope or longline from which the breeding ropes  
are hanging and which is maintained in a horizontal position  
once extended and grounded by means of weights anchored on  
5 the sea floor, while subjected to the uplift force exerted  
by a plurality of buoys or floats to which it is attached in  
combination with a plurality of surface floats, ~~said~~ the  
live well is provided with an improved support and beaconing  
facility.

10               These already existing installations, in  
particular those with self-supporting flotation buoys, have  
proven their open sea capabilities but have the drawback  
that the impact of the waves and the weight of the load  
during vertical movement can not only cause the detachment  
15 of the animals due to rupture of the supporting byssus, but  
can also result in exhausting or stressful situations for  
some breeding species.

              Although these open sea installations allow  
mooring the ship to the longline to facilitate collection of  
20 the harvest, no description is available in respect to the  
handling of the longline which we suppose is raised by  
crane, normally a difficult procedure.

              A further negative effect on the crop is caused by  
the necessary maintenance of the line at a height normally

equidistant to the seabed, this being established depending on both the length of the chains used to connect the ends of the longline to the dead weights holding ~~said~~ the chains to the sea floor as well as the upwards lift from the floaters.

5

#### OBJECTS AND SUMMARY OF INVENTION

It is one aim of the present invention to enable the breeding of shellfish in open sea and to provide suitable conditions for adapting to the swell, the tide and  
10 even the possible maritime traffic. A further aim is to avoid the occurrence of those sudden vertical movements, which traditional farms suffer from and which cause the detachment or exhaustion of the animals. In addition, the farm is designed in such a way that the collection or  
15 laboring of the crop can take place with no manual intervention.

The above-mentioned aims are achieved in the improved submersible farm according to the present invention by suspending the line of cables and the cylindrical buoys  
20 that maintain ~~said~~ the line horizontally from the end floats which comprise a filling/draining system using water by way of ballast, in order to lift or submerge the line by inflating ~~said~~ the floats with air. Further, the present invention relates to an anchoring system using submerged

tension buoys that are connected to the aforementioned floats by means of tension cables and pulleys which are fixed to the dead weights provided at either end of the line. The vertical thrust of the above-mentioned tension  
5 buoys causes the pulley to stretch the cable and tauten the line.

This object is achieved by means of an improved submersible shellfish farm comprising at least one line of cables bearing spaced ropes to which the shellfish are  
10 attached for their rearing., ~~said~~ The line being is suspended horizontally from two end floats which support ~~it~~ the line in association with intermediate support buoys and is further anchored by dead weights positioned at each end of the line. An essential characteristic of the  
15 aforementioned at least one line of cables is its ability to be submerged and located at any position elevated in relation to the sea floor while guided by the vertical movement of the above-mentioned end floats when they are in a submerged state., ~~said~~ The end floats being are capable  
20 of being submerged or raised as a consequence of their inner volume being variable by filling or draining ~~said the~~ volume of water or air, ~~and being those~~ The end floats are connected to a surface buoy comprising an air intake valve and are also connected to the aforementioned concrete dead

weights by an anchoring system which maintains the line tension.

A further essential characteristic is that ~~said~~ the anchoring system comprises at least the respective end  
5 buoys conveniently submerged and arranged so as to use their uplift thrust to pull at each of ~~said~~ the end floats to which they are respectively connected by means of tensioning cables and pulleys fixed to ~~said~~ the concrete dead weights.

The end floats from which the line of cables  
10 bearing the culture ropes is suspended and the cylindrical  
buoys that maintain the line horizontally comprise a  
filling/drainning system using water by way of ballast in  
order to lift or submerge the line by inflating the floats  
with air. Submerged tension buoys, connected to the floats  
15 by means of tension cables and pulleys which are fixed to  
the dead weights provided at either end of the line, create  
a vertical thrust which causes the pulley to stretch the  
cable and tauten the line.

20 BRIEF DESCRIPTION OF THE DRAWING

The sole figure shown in the illustration sheet  
shows a perspective view of an improved submersible farm in  
accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention relates to an improved submerged farm comprising a line formed by at least two parallel cables and suspended between two end floats which  
5 act as a support for ~~said the~~ line. ~~said The~~ end floats are supplied with air through a pneumatic hose connected to an air intake valve which is mounted on a surface buoy. The described assembly is anchored by means of dead weights located at each end of the line and in close proximity to  
10 the aforementioned end floats respectively, to which two submerged tension buoys are attached by means of a cable and a pulley fixed to the dead weight, ~~said The~~ tension buoys ~~creating~~ create a vertical thrust which causes the stretching of the cable and tautening of the line.

15 According to the present invention, the culture ropes are suspended from each of the cables forming the line of cables in such a way that spaces are left between each of ~~said the~~ ropes and occupying each of ~~said the~~ spaces and suspended between both parallel cables, cylindrical buoys  
20 are suspended to ensure that the submerged line of cables is maintained in a horizontal position, while avoiding the creation of a catenary. In the same manner as the end floats, these buoys are supplied with the air circulating through the pneumatic hose in such a way that pressurized

air can be injected into ~~said~~ the buoys to remove the ballast water or, alternatively, leaving the air to escape to enable the inflow of water into them. This method enables the adjustment of the depth at which the line is to  
5 be maintained or the raising of the line to the surface for collection or laboring.

~~said~~ The cylindrical buoys are advantageously mounted underneath of the cables so that they raise the line until the grips of the culture ropes are left outside the  
10 water.

According to a preferred embodiment of the present invention, the farm ~~consists of~~ includes a line of cables bearing culture ropes and being suspended between two end floats, which are anchored to respective concrete dead  
15 weights. Preferably, each end float, or at least one of the two, is connected to a surface beacon buoy fitted with a system to supply pressurized or atmospheric air to the end floats, ~~said~~ The system ~~including~~ includes at least one air intake valve and one pneumatic hose.

20 The farm is advantageously anchored by means of dead weights located at each end of the line and in close proximity to the aforementioned end floats respectively, to which two submerged tension buoys are attached by means of a cable and a pulley fixed to the dead weight, ~~said~~ The

tension buoys ~~creating~~ create a vertical thrust which causes the stretching of the cable and tautening of the line.

The culture ropes are conveniently suspended from each of the cables in the line in such a way that cylindrical  
5 buoys are suspended between both parallel cables, occupying the spaces between the ropes and ensuring that the submerged line of cables is maintained in a horizontal position, while avoiding the creation of a catenary. In the same manner as the end floats, these buoys are supplied with the air  
10 circulating through the pneumatic hose in such a way that pressurized air can be injected into ~~said~~ the buoys to remove the ballast water or, alternatively, leaving the air to escape to enable the inflow of water into them. This method enables the adjustment of the depth at which the line  
15 is to be maintained or the raising of the line to the surface for collection or laboring.

The culture ropes are normally suspended along each of the cables in the line, maintaining a distance of one and a half meters between them and held in that position  
20 by suitable stops. Preferably, every five meters of the line, buoys are positioned underneath of the cables to join them and to maintain the line in a substantially horizontal position.

According to the example, the culture ropes



incorporate a hoop with a handle, a gravity actuated  
snaphook and a ring to which the aforementioned culture rope  
is fastened.

The selection of the anchoring system will depend  
5 on the location where the farm is installed. By way of  
example, a preferred embodiment appropriate for locations  
with low tide is realized by placing at each end of the line  
of cables a submerged buoy anchored to a dead weight with a  
line, and which function it is to maintain the line tension  
10 by means of a pulley mounted on the concrete dead weight. A  
chain joins the submerged buoy and the surface buoy while  
providing a means of anchoring for ~~said~~ the buoy. A cable  
holding the hose connects the beacon buoy with a linking  
element, which joins the tensioning cable from the anchor  
15 buoy and a set of hinged bars that have the function of  
preventing the main buoys from capsizing.

Notwithstanding the above example, in a second  
embodiment suitable for locations with high tide, the  
anchoring system could comprise level buoys secured on the  
20 end floats of the farm line in combination with the  
tensioning buoys.

The example illustrates how ~~said~~ the cylindrical  
buoys are advantageously mounted underneath of the cables so  
that they raise the line until the grips of the culture

ropes are accessible outside the water.

To facilitate comprehension of the ideas presented here, a preferred embodiment of the present invention is given below, with reference to the accompanying illustrative  
5 drawings, which shall not limit by their selection or graphical representation the advantages and particular characteristics of this application.

The sole figure shown in the illustration sheet shows a perspective view of one of the end parts of an  
10 improved submersible farm in accordance with this invention, which is represented schematically so as to provide a better view.

The figure shows, suspended from the end float (1), a line of parallel cables (2 and 3) bearing culture  
15 ropes (4) which are conveniently separated from each other by means of positioners (5) while being supported by cylindrical buoys (6).

The end floats (1) and the corresponding cylindrical buoys (6) are joined by means of a pneumatic  
20 hose (7) which in turn is connected to an air intake (8) mounted on a beaconed surface buoy (9).

In the embodiment shown, the end float (1) is anchored to a concrete dead weight (10) or an anchor of similar type, to which it is connected by means of a

6463/PCT/USSN 10/519,165  
Group Art Unit 3644

tensioning cable (11) running on a pulley (12) attached to  
~~said~~ the dead weight and which connects it to a tensioning  
buoy (13) which is linked to the dead weight (10) by a fixed  
line (14) and to the surface buoy (9) by the anchor chain  
5 (15).

A cable (16) to which the pneumatic hose is  
attached joins the surface buoy ~~(8)~~ (9) and the linking  
element (17), the latter also joining the end of the  
tensioning cable (11) and the bars (18) which aid in  
10 preventing the end floats (1) to capsize.

6463/PCT/USSN 10/519,165  
Group Art Unit 3644

SUMMARY

~~IMPROVED SUBMERSIBLE FARM~~

~~The end floats from which the line of cables bearing the culture ropes is suspended and the cylindrical~~  
5 ~~buoys that maintain said line horizontally comprise a filling/drainage system using water by way of ballast in order to lift or submerge the line by inflating said floats with air. Submerged tension buoys, connected to the floats by means of tension cables and pulleys which are fixed to~~  
10 ~~the dead weights provided at either end of the line, create a vertical thrust which causes the pulley to stretch the cable and tauten the line.~~

ABSTRACT

~~The invention relates to an~~ An improved  
submersible mollusc farm is disclosed. ~~According to the~~  
~~invention, a~~ A line of cables bearing the culture ropes and  
5 the cylindrical buoys which maintain ~~said~~ the line  
horizontal is suspended from end floats. The end floats  
~~comprise~~ include a filling/emptying system using water by  
way of ballast, in order to raise or submerge the line by  
inflating ~~said~~ the end floats with air. Submerged tension  
10 buoys are connected to the ~~aforementioned~~ end floats by  
~~means of~~ tension cables and pulleys which are fixed to the  
dead weights provided at either end of the line. The  
vertical thrust of the ~~above-mentioned~~ tension buoys causes  
the pulley to stretch the cable and tauten the line.